

ColorSpot 1200E AT™

The ColorSpot 1200E AT is an electronic ballast version of ColorSpot 1200 AT, which adds even more features like flicker-free operation, enhanced light output, extended lamp life, power-saving mode for economy and reduced weight.



Technische Spezifikation

Lichtquelle

- Lamp: 1200 W short arc discharge
- Base: GY22
- Approved model: Philips MSR 1200 SA
- Control: Automatic and remote on/off
- Ballast: Electronic

Elektrische Spezifikationen und Anschlüsse

- Wiring options: 100/120/208/230/250 V, 50-60 Hz
- Power consumption: 1600 VA at 230 V/50 Hz
- Automatic voltage and frequency selection for lamp

Mechanische Spezifikationen

- Height: 619 mm (24.4 ") - head in horizontal position
- Width: 536 mm (21.1 ")
- Depth: 616 mm (24.3 ")
- Weight: 42 kg (92.6 lbs)

Thermische Spezifikation

- Maximum ambient temperature (Ta): 40 °C (104 °F)
- Maximum surface temperature: 135 °C (275 °F)

Rotierbare Gobos

- Dichroic glass gobos - outside diameter: 37.3 mm, image diameter: 31.5 mm, thickness: 1.1 mm, max. thickness: 5 mm, high temperature borofloat or better glass, coating: dichroic or enhanced aluminium
- Glass gobo - outside diameter: 37.0 mm, thickness: 1.1 mm, max. thickness: 5 mm, high temperature borofloat or better glass

Optisches System und Effekte

- Outside diameter: 47 +0/-0.3 mm
- Thickness: Up to 5 mm in rotating slots (up to 8 mm in the center)

Steuerung und Programmierung

- Protocol: USITT DMX-512, RDM support
- Control channels: 24 or 323 DMX control modes
- Setting & Addressing: ROBE Navigation System (RNS)
- Display: Blue/white LCD graphic
- Pan/Tilt resolution: 16bit
- Gobo indexing: 8 or 16bit
- Prism indexing: 8 or 16bit
- Dimmer: 8 or 16bit
- Movement control: Tracking and vector
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Lamp power save mode while black-out
- Stand-alone operation
- 3-editable programs, each up to 99 steps

Elektromechanische Effekte

- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%
- CTO: 0-100%
- Colour wheel: 6 replaceable "SLOT&LOCK" colours + open
- Gobo wheel 1:6 rotating, indexable, replaceable "SLOT&LOCK" dichroic glass gobos + open
- Gobo wheel 2:6 rotating, indexable, replaceable "SLOT&LOCK" dichroic glass gobos + open
- Iris: Motorized, stepless
- Effect wheel: 4 rotating, indexable, replaceable "SLOT&LOCK" prisms and effects + open
- Frost effect: Separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect, ZAP effect (electronic strobing)
- Focus: 2 m - infinity
- Zoom: 13° - 42°
- Pan: 530°
- Tilt: 280°

Rigging


- Mounting points: 8 pairs of ¼-turn locks
- Fastening system: ROBE's own 2x Omega clamps
- Fixation option: Pan/Tilt-lock mechanism

Zubehör


- Remote control IR

Gobos&Farben

Rotierbares Goborad 1




15020125



15020124




15020123



15030014



15030013




15030012


Rotierbares Goborad 2



15020130




15020129



15020128




15020127




15020126

Farbrad



14070121




14070119



14070118



14070120



14070123



14070122