

CityScape 48™

The CityScape 48 is a durable and robust fixture with a projected lifespan of at least 60,000 hours. The base is made from cast metal and includes an inbuilt power supply and an intelligent LED driver.



The fixture's head is made up of a cast aluminium radiator onto which the LED matrix and lenses are fitted. The head can be tilted in relation to the base in range of 145°.

Technische Spezifikation

Optisches System & Effekte

- Light source: 48 high power RGBW Luxeon Rebel LEDs
- Standard optical system: 12° beam angle and eggcrate lens module 25°, banddoors included
- LED life expectancy (according to B10L70 criterion): 60,000 hrs (Eco mode), 15,000 hrs (High power mode)
- RGBW colour mixing
- Built-in colour macros
- Adjustable strobe sequences
- White colour balance adjusting
- Pre-programmed random strobe pulse-effects

Steuerung und Programmierung

- Control panel: 4-digit LED display and four control buttons
- Control: USITT DMX 512 (RDM support)
- DMX protocol modes: 4 (2, 3, 4, 8 control channels)
- Operations modes: DMX, Stand-alone, Master/Slave
- Manual control of all effects via control panel
- 3 user editable programs each up to 68 steps
- Smooth 16-bit dimming from 0-100 %
- Optional wireless version available: CRMX™ technology from Lumen Radio

Thermische Spezifikation

- Maximum ambient temperature: 40 °C
- Maximum housing temperature: 80 °C

Elektrische Spezifikationen und Anschlüsse

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V AC, 50-60 Hz
- DMX data IN: 1.3 m long cabel with 5-pin Indoor XLR (male)
- DMX data OUT: 1.3 m long cabel with 5-pin Indoor XLR (female)
- Power: 1.4 m long power cabel without plug

Leistungsaufnahme

- Height: 173 mm (6.8")
- Width: 243 mm (9.6")
- Depth: 172 mm (6.8")
- Head position adjustment range: 145°
- Weight: 3 kg (6.6 lbs)
- Protection factor: IP 65

Mechanische Spezifikationen

- Height: 173 mm (6.8")
- Width: 243 mm (9.6")
- Depth: 172 mm (6.8")
- Head position adjustment range: 145°
- Weight: 3 kg (6.6 lbs)
- Protection factor: IP 65

Rigging

- Omega clamp + adapter for Omega clamp

Zubehör

- Eggcrate lens module 45°
- Eggcrate lens module 45°x15°
- Eggcrate top hat module (without lenses)
- Quad Top-loader case (without castors)
- Octuple Top-loader case