

REDBlinder 2•96™

The REDBlinder 2•96 is fitted into the industry standard 8-lite casing and offers set and lighting designers all the options. REDBlinder is a LED version of the popular 8-lite Molefay, a staple of the rock "n" roll world, featuring 8 LED modules, each with 12 RGB K2 LEDs. Each four pairs of modules are separately controllable. This product is aimed at all stage lighting markets and television productions and for arenas and larger venues.



Technische Spezifikation

Lichtquelle

- High-Power Luxeon K2 LEDs
- 32 Red K2 LEDs, 32 Green K2 LEDs, 32 Blue K2 LEDs
- Min. 50.000 hrs Rated Life

Abstrahlwinkel

- 25° beam angle of each LED

Frost, Diffusion

- Optional frost filters (glass or film) for even light distribution

Farben

- 16.7 million colours (24 bit)
- Pre-programmed colours & rainbow effect
- Dynamic colour balance between white and red, green, blue colours during production
- White balance pre-programmed via LED control panel

Dimmer, Strobe

- Electronic dimmer for light output adjustment from 0 to 100%
- High speed white or full colour strobe, flash rate 1-25 fps

Mechanische Spezifikationen

- Height: 810 mm (31.9")
- Width: 480 mm (18.9")
- Depth: 190 mm (7.5")
- Weight: 18 kg (39.7 lbs)

Thermische Spezifikation

- Maximum ambient temperature: 40°C (104°F)
- Maximum housing temperature: 80°C (176°F)

Steuerung und Programmierung

- Protocol: USITT DMX-512
- Control options: DMX, Auto-trigger
- Operation modes: Master/Slave, Stand-alone
- Programs: 6 built-in programs + 3 user editable programs up to 30 steps each
- Display: 4 digit LED
- Manual control of all DMX channels via LED control panel
- 4 pairs of LED modules

DMX Kanäle

- Mode 1: 15 channels
- Mode 2: 12 channels
- Mode 3: 6 channels
- Mode 4: 3 channels

Verbindung

- Control: DMX 512
- DMX connection: 3-pin or 5-pin XLR-sockets

Leistungsaufnahme

- Input Voltage: 100-240 V, 50/60 Hz
- Max. Power Consumption: 260 VA

Zubehör

- Set glass frost
- Set film frost