

ROBIN[®] 600E Spot[™]

The ROBIN 600E Spot has a dramatically increased light output (from the 300 Series) and lower power requirements - thanks to an optimized optical path made from carefully selected components.



The super strong light-output can be maximised by using ROBE's unique HotSpot Control system together with the linear iris to create very powerful beam effects. An innovative patented cooling system ensures the best lamp operating temperatures and allows DMX controlled noise reduction. Users have complete control of all features of this fixture, making it ideal for environments where noise levels are critical and light output requirements are high.

Technische Spezifikation

Lichtquelle

- Lamp: Compact high-pressure metal halide lamp
- Base: PGJX28
- Approved model: Philips MSR Gold 575/2 MiniFastFit
- Control: Automatic and remote on/off
- Ballast: Electronic

Optisches System

- Optical system
- Dichroic glass reflector for maximising the light efficiency
- Beam angle: Zoom range: 10° - 45° (2° - min. zoom with iris, 60° max. zoom with frost)

Elektromechanische Effekte

- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%
- CTO: 0-100%
- Hot-spot control: Hot-or-not-spot
- Colour wheel: 7 replaceable "SLOT&LOCK" dichroic filters + open, trapezoid shape
- Static Gobo wheel: 9 replaceable "SLOT&LOCK" black and white gobos + open
- Rotating Gobo wheel: 7 rotating, indexable, replaceable "SLOT&LOCK" dichroic and glass gobos + open Iris:
Motorized, stepless, up to 3 Hz
- Prism: 3-facet 11° indexable prism rotating in both directions at different speeds
- Frost effect: Separate, variable
- Dimmer/Shutter: Full range dimming and variable strobe effect, Electronic strobbing "ZAP"
- Motorized zoom and focus
- Pan: 540°
- Tilt: 280°

Steuerung und Programmierung

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2
- Control channels: 23, 25, 32 3 DMX protocol modes
- 3-editable programs, each up to 100 steps
- Stand-alone operation
- QVGA Robe touch screen with battery backup gravitation sensor for auto screen positioning operation memory service log with RTC
- Pan/Tilt resolution: 8 or 16 bit
- Movement control: Tracking and vector
- Colour wheel positioning: 8 or 16bit
- Static gobo wheel positioning: 8 or 16bit
- Rotating gobos: 8 or 16bit
- Iris: 8 or 16bit
- Frost: 8 bit
- Focus: 8 or 16bit
- Dimmer: 8 or 16bit
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin & 5-pin XLR
- Built-in analyser for easy fault finding
- Optional wireless version available: CRMX™ technology from Lumen Radio

Statische Gobos

- Metal gobos - outside diameter: 26.9 mm, image diameter: 22.5 mm, aluminium, thickness: 0.5 mm
- Glass gobo - high temperature borofloat

Rotierbare Gobos

- Glass gobos - outside diameter: 26.8 mm, image diameter: 22.0 mm, thickness: 1.1 mm, max. thickness: 4.0 mm, high temperature borofloat or better glass

Thermische Spezifikation

- Maximum ambient temperature: 45 °C (104 °F)
- Maximum surface temperature: 80 °C (176 °F)

Elektrische Spezifikationen und Anschlüsse

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption: 770 VA at 230 V/50 Hz

Mechanische Spezifikationen


- Height: 516 mm (20.3 ") - head in horizontal position
- Width: 433 mm (17.0 ")
- Depth: 470 mm (18.5 ")
- Weight: 21.7 kg (47 lbs)
- Fixation option: Pan/Tilt-lock mechanism

Rigging

- Mounting points: 2 pairs of ¼-turn locks
- 2 x Omega bracket with ¼-turn quick locks
- Safety chain/rope attachment point

Gobos&Farben


Rotierbares Goborad



15020216



15020217




15020218



15020219



15020220



15020221



15030029

Farbrad



99011881




99011882




99011884



99011883



99011887



99011886



99011885

Statisches Goborad




15010734



15010720



15020222



15010735



15010728




15010730



15010736



15010737



15010738