

RecessedWash 150 AT

RecessedWash 150 AT is ideal for architectural lighting, bars, restaurants, clubs, retail stores, churches, exhibit halls and for all other ceiling-mount applications. The RecessedWash 150 is a ceiling-mount version of Wash 150 XT with all functions of the popular Wash 150 XT moving head. Its colour wheel offers 10 dichroic slots plus open, and it has a dimmer and shutter. It uses a 150 Watt CDM lightsource from Philips.



Technische Spezifikation

Lichtquelle

- Lamp: Compact discharge lamp
- Base: G-12
- Approved model: Philips CDM-SA/T 150/942
- Ballast: Magnetic

Optisches System

- 21° beam angle

Elektrische Spezifikationen und Anschlüsse

- Wiring options - EU - model: 208/230/240V AC, 50/60Hz, Wiring options - US - model: 100/120/208/230/240V AC, 50/60Hz
- Power consumption: 300 VA at 230V/50Hz

Mechanische Spezifikationen

- Height (including ceiling box): 410 mm (16.1") - head in horizontal position
- Width (including ceiling box): 595 mm (23.4")
- Depth (including ceiling box): 593 mm (23.3")
- Weight - moving head: EU model 10 kg (22.0 lbs)
- Weight - moving head: US model 12 kg (26.4 lbs)
- Weight-ceiling box: 7kg (15.4 lbs)

Thermische Spezifikation

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

Steuerung und Programmierung

- Protocol: USITT DMX-512
- Control channels: 6 – 8 DMX, 4 protocol modes
- Built-in demo sequences
- Display: 4-digit LED display
- Pan/Tilt resolution: 8- or 16-bit
- Master/slave operating
- 4 DMX channel-presettings
- Movement control: Tracking and vector
- Built-in analyzer for easy fault finding
- Data in/out: Locking 3-pin XLR
- built-in microphone for audio mode

Elektromechanische Effekte

- Colour wheel: 11 dichroic filters + open
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Pan: 530°
- Tilt: 280°
- Maximum Pan-movement 530° in 3 s
- Maximum Tilt-movement 280° in 1.9 s

Rigging

- Ceiling box for 600x600 mm grid mounting
- Integral attachment points for wire hangers or all-thread support