

# Ecolor 250 XT

The Ecolor 250 XT includes a 250W discharge lamp, manual zoom with beam angle range from 8° to 22°, full CMY colour mixing. The dimmer unit allows the fixture very smooth micro-step driven diming. The fixture is an ideal tool for outdoor architectural lighting.



# Technische Spezifikation

## Technische Spezifikationen

- Wiring options-EU model: 208/230/240V AC, 50/60 Hz
- Wiring options-US model: 100/120/208/230/240V AC, 50/60 Hz
- Power Consumption: 450 VA
- Lamp: Philips MSD 250/2
- Beam Angle: 8°-22° (manually adjustable)
- CMY colour mixing system: cyan 0-100%, magenta 0-100%, yellow 0-100%
- Manually adjustable effects: horizontal and vertical beam shaper, frost filter and 3200K CTF
- Dimmer/Strobe: full range dimming, variable strobe effect
- Tilt: 130° (manually adjustable)
- Protocol: USITT DMX 512
- Control channels: 6
- Control Options: DMX, Time-trigger, Light-trigger
- Operation modes: DMX, Master/slave, Stand-alone
- Display: 4-digit LED
- Programs: 3 user editable programs up to 99 steps each
- Data in/out: Locking 3-pin XLR
- Max. ambient oper. temp.: 35°C (95°F)
- Mounting points: 2 mounting slots
- Weight (head): 22 kg (EU version)
- 24.5 kg (US version)
- Accessories: remote control