

LEDBlinder 148 LT

The LEDBlinder 148 LT is a 4-way version of the LEDBlinder 196 LT. The unit is fitted into the industry standard 4-lite casing and offers set and lighting designers all the options. It has 4 LED modules, each with 12 RGB LEDs. Each two pairs of modules are separately controllable. This product is aimed at all stage lighting markets and television productions and for arenas and larger venues.



Technische Spezifikation

Lichtquelle

- High-Power 1W Luxeon LEDs
- 16 Red LEDs, 16 Green LEDs, 16 Blue LEDs
- < 50.000 hrs Rated Life

Abstrahlwinkel

- 25° beam angle of each LED

Frost, Diffusion

- Optional frost filters (glass or film) for even light distribution

Farben

- 16,7 million colours (24 bit)
- Pre-programmed colours & rainbow effect
- Dynamic colour balance between white and red, green, blue colours during production
- White balance pre-programmed via LED control panel

Dimmer, Strobe

- Electronic dimmer for light output adjustment from 0 to 100%
- High speed white or full colour strobe, flash rate 1-25 fps

Mechanische Spezifikationen

- Height: 510 mm (20.0")
- Width: 480 mm (18.9")
- Depth: 190 mm (7.5")
- Weight: 12 kg (26.5 lbs)

Thermische Spezifikation

- Maximum ambient temperature: 40°C (104°F)
- Maximum housing temperature: 60°C (140°F)

Steuerung und Programmierung

- Protocol: USITT DMX-512
- Control options: DMX, Auto-trigger
- Operation modes: Master/Slave, Stand-alone
- Programs: 6 built-in programs + 3 user editable programs up to 30 steps each
- Display: 4 digit LED
- Manual control of all DMX channels via LED control panel
- 2 pairs of LED modules

DMX Kanäle

- Mode 1: 9 channels
- Mode 2: 6 channels
- Mode 3: 6 channels
- Mode 4: 3 channels

Verbindung

- Control: DMX 512
- DMX connection: 3-pin or 5-pin XLR-sockets

Leistungsaufnahme

- Input Voltage: 100-240 V, 50/60 Hz
- Fuse: T 2A
- Max. Power Consumption: 70 VA

Zubehör

- Set glass frost
- Set film frost