

LOW FOG 3000 FT™

Distinguishing itself from other products currently on the market, the FOG 3000 FT™ creates low fog straight from machine's nozzle.



This makes it far more efficient and convenient without any hassles of CO2 installations and other attachments. It is operator-friendly as there are no external controls to the machine. Simply plug the unit in, connect the 3M fog conducting hose (for remote dispersion) and operate it like a normal fog machine. There is no pollution or harmful effects to the environment or human body, making LOW FOG 3000 FT™ a true green machine, especially pertinent with today's environmental and health concerns. The effects produced is virtually indistinguishable from that created by dry ice. A powerful compressor, aluminum heating block and 3 step variable output enables selection of 'tiny cloud' to the thickest fog. It is fully controllable via a LCD DMX 512 controller allowing precise control of time and volume. Furthermore, the after-service maintenance is trouble-free as the compressor and the heater are in two different self contained locations. Electricity is saved due to the highly efficient power control system and superior ventilation, thus permitting the fogger to operate at optimal low-level temperatures. The 10-liter tank also offers nonstop power and extended use between refills. LOW FOG 3000 FT™ will be an impressive effect for theatrical and studio applications where low noise levels and environment/health issues are crucial.

Technische Spezifikation

Beschreibung

- Power: AC 230 V/AC 240 V, 50Hz or AC 100 V/AC 120 V/60 Hz optionally
- Power Consumption (Compressor): 750 W @ 120 V, 600 W @ 230 V
- Refrigerant: R-404 A, 1.75LB
- Rated Current: 6.7 A @ 120 V, 3.2 A @ 230 V
- Start Current: 61 A @ 120 V, 21 A @ 230 V
- Heater: 1450 W @ 120 V, 2500 W @ 230 V
- Output: 12,000 cu.ft/min
- Fluid Consumption Rate: 11 min/l (100% Output)
- First Heat-Up Time: 24 min @ 120 V, 12 min @ 230 V
- Tank Capacity: 10 liters
- Remote Included: LCD Timer Panel Controller; 2 Meters
- Accessory Included: 3M Fog Conducting Hose
- Weight: 120 kg
- Dimensions (mm): L 780 x W 608 x H 688
- Liquid Used: Premium Fog, Performance Fog
- DMX Channel DMX: One Channel
- DMX on board

Zusätzliche Informationen

- Self Contained Unit - CO2 / Dry Ice are NOT REQUIRED
- Floor-Mount installations (4 wheels)